



DB9M(NICKEL PLATED)
BLACK ASSEMBLY SHELL

OPEN/SHORT TEST:100% TEST.
INSULATION: MIN. 10M.

PIN ASSEMBLY:

| P1 | P2 |
|----|----|
| 1 | 1 |
| 6 | 2 |
| 2 | 3 |
| 7 | 4 |
| 3 | 5 |
| 8 | 6 |
| 4 | 7 |
| 9 | 8 |
| 5 | 9 |
| × | 10 |

| | | |
|-----|--|------|
| 6 | Metal bracket L=12CM | 1PCS |
| 5 | COPPER CYLINDER H4.75*11.8MM | 2PCS |
| 4 | IDC10P BLACK Three Pieces with Nose | 1PCS |
| 3 | BLACK ASSEMBLY SHELL+2PCS SCREW NUT | 1PCS |
| 2 | DB9M (BLACK INSULATOR,NICKEL PLATED) | 1PCS |
| 1 | 28AWG UL2651,10C PH2.54 Gray PVC Jacket (28#TA) | 1PCS |
| No. | Description | Q'ty |

| | | | | | | | |
|--------------|--------|------------------|--|----------|-----|------|------------|
| Company | | Goods Code | | Draw | DRL | Date | 2016.11.22 |
| ITEM NO. | AK3326 | Drawing Evidence | | Check | | Date | |
| Goods NO. | | | | Approval | | Date | |
| Original NO. | | Unit(mm) | | Audit | | Date | |

| | | |
|--------|--------|------|
| D | | |
| C | | |
| B | | |
| VER. A | REVISE | Date |