



Introduction

The Atlona **AT-HDVS-150-TX** is a 3×1 switcher and HDBaseT transmitter with two HDMI inputs and a VGA input with audio. Video signals up to 1080p, plus embedded audio can be transmitted up to 230 feet (70 meters). The HDVS-150-TX is designed for use with the AT-HDVS-150-RX receiver and HD scaler, and can serve as the central component of a compact, automated AV system with the convenience of automatic input selection and display control. The switcher is remotely powered by the HDVS-150-RX through Power over Ethernet (PoE).

The HDVS-150-TX combines the benefits of auto-switching and integrated display control, and the advantages of HDBaseT signal transmission. It incorporates many popular integration convenience features while delivering excellent value for classrooms, huddle rooms, and meeting spaces.

Surface mounting brackets are provided with the HDVS-150-TX for easy under-table, furniture, or on-wall installation.

The Atlona **AT-HDVS-150-TX-PSK** is identical to the AT-HDVS-150-TX, with the addition of local powering capability and an external power supply. This makes it ideal for extending AV and control directly to a projector with an HDBaseT input. The AT-HDVS-150-TX can serve as the central component of a small, automated AV system through automatic input selection, and by sending RS-232 control commands to the display. With automatic display control capability, the AT-HDVS-150-TX can power the display on or off whenever a source is connected or disconnected from the unit.

Applications

- Education environments
- Corporate environments

Key Features

3x1 HDBaseT switcher

- Features two HDMI inputs plus a VGA input with audio.⁽¹⁾
- Allows advanced HDMI display devices to be used with legacy VGA sources.

Designed for point-to-point extension to the AT-HDVS-150-RX HD scaling receiver

- Extends AV up to 230 feet (70 meters) @ 1080p or 1920x1200.
- Provides a cost-effective yet compact, automated AV system with the convenience of automatic input selection and display control.

Long distance HDMI extension

- Transmits AV up to 230 feet (70 meters) @ 1080p or 130 feet (40 meters) @ 4K/UHD⁽²⁾ using CAT6a/7 cable
- Uses easy-to-integrate category cable for low-cost, reliable system installation

Remotely powered via PoE (Power over Ethernet)

- IEEE 802.3af PoE Powered Device (PD).
- Power for transmitter is supplied by AT-HDVS-150-RX over HDBaseT.

Automatic input selection using hot plug detection

- Selects active input when sources are connected or if there is a change in source power status.
- Enables simplified, automatic system operation with no user intervention necessary.

Automatic display control (when connected to the HDVS-150-RX)

- Automatically changes display power state based on active or standby mode of the switcher (in conjunction with the HDVS-150-RX). Control signals to display are transmitted via RS-232.
- Eliminates the need for a complex control system.

Front panel input selection and on/off controls

- Overrides auto-switching when more than one active source is present.
- Simple manual operation allows presenter to maintain control of AV system.

Field-updatable firmware

- Rear panel USB port provides an easy means for device updates.
- Ensures long-term system return on investment.

Front panel power and input selection status LEDs

- LED indicators provide power and input selection status information.
- Provides easy setup and troubleshooting.

Included accessories

- User guide and surface mounting brackets.
- Power supply (**AT-HDVS-150-TX-PSK** only) - ideal for point-to-point installations with an HDBaseT-equipped projector.

Award-winning 10 year limited product warranty

- Ensures long-term product reliability and performance in commercial and residential systems.
- Specify, purchase, and install with confidence.

Specifications

Video		
Signal	HDMI	
Copy Protection	HDCP 1.4	
Pixel Clock	300 MHz	
UHD/HD/SD	4096x2160@60 ⁽³⁾ /50/30/25/24Hz 3840x2160@60 ⁽³⁾ /50/30/25/24Hz 1080p@60/59.9/50/30/29.97/25/ 24/23.98Hz 1080i@30/29.97/25Hz	720p@60/59.94/50Hz 576p@50Hz 576i@25Hz 480p@60/59.96Hz 480i@30Hz
VESA All resolutions are 60Hz	2560x1600 2048x1536 1920x1200 1680x1050 1600x1200 1440x900 1400x1050 1280x1024	1280x800 1366x768 1360x768 1152x864 1024x768 800x600 640x480
Color Space	YUV, RGB	
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0	
Color Depth	8-bit, 10-bit, 12-bit	

Audio	
HDMI	PCM 2.0
Bit Depth	up to 24-bit
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz

CEC	
Port	1 x HDMI, Type A, 19-pin female
Triggering	RS-232

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
HDMI IN	15	5	30	10
CAT5e	115	35	200	60
CAT6/6a/7	130	40	230	70

Buttons and Indicators	
Buttons: DISPLAY ON/OFF, INPUT SELECT	2 x push buttons, momentary, tact-type
Indicators: PWR, HDMI 1, HDMI 2, VGA	4 x LED, green

Connectors	
HDMI IN	2 - Type A, 19-pin female
VGA IN	1 - 15-pin, VESA female
HDBaseT OUT	1 - RJ45
AUDIO IN	1 - 3.6 mm, stereo
DC 48V (PSK only)	1 - 2-pin, captive screw

Environmental	
Operating Temperature	+32 to +122 °F 0 to +50 °C
Storage Temperature	-4 to +140 °F -20 to +60 °C
Operating Humidity (RH)	+20 to +90%, non-condensing

Power	AT-HDVS-150-TX	AT-HDVS-150-TX-PSK
Consumption	18.7 W (when paired)	18.7 W (when paired)
Idle Consumption	N/A	22 W
Supply	N/A	Input: 100 - 240 V AC, 50/60 Hz Output: 48 V DC, 3.125 A
Safety	N/A	CE, FCC, cULus

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.50 x 5.00 x 4.02	38 x 127 x 102
Power Supply (AT-PS-48083-D3) ⁽⁴⁾	1.42 x 1.81 x 4.41	36 x 46 x 112

Weight	Pounds	Kilograms
Device	0.64	0.29

Certification	
Device	CE, RoHS, FCC

Footnotes

- (1) Audio signals will not pass without an accompanying video signal.
- (2) Allows 4K/UHD transmission when used with a compatible HDBaseT receiver.
- (3) 4096x2160@50/60Hz & 3840x2160@50/60Hz supported @ chroma subsampling 4:2:0 8-bit only.
- (4) Only included with AT-HDVS-150-TX-PSK.

Copyright, Trademark, and Registration

© 2021 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI licensing Administrator, Inc.