



## Introduction

The Atlona AT-OPUS-RX is an HDBaseT receiver for high dynamic range (HDR) formats, designed for use with the Opus™ Series of HDMI to HDBaseT matrix switchers. The OPUS-RX is HDCP 2.2 compliant and supports 4K/UHD video @ 60 Hz with 4:4:4 chroma sampling, as well as HDMI data rates up to 18 Gbps. It receives HDMI, Ethernet pass-through, and bidirectional IR and RS-232 control signals up to 330 feet (100 meters) over CAT6a/7 cable. Visually lossless VESA Display Stream Compression (DSC) enables HDR and 4K/60 4:4:4 video signal extension over HDBaseT with no latency. For additional integration convenience, the receiver is remotely powered by an Opus Series matrix switcher through Power over Ethernet (PoE). The OPUS-RX can transmit digital audio from a television back to an AV receiver through a dedicated HDBaseT audio return path to the matrix switcher.

## Applications

- **Residential installations**  
 An Opus system of matrix switchers and OPUS-RX receivers is ideal as the AV distribution centerpiece for whole-house video and audio.
- **Commercial applications**  
 Opus systems are also ideal for a variety of light commercial, education, and corporate applications requiring compatibility with new and forthcoming devices for 4K presentations.

## Key Features

### 4K/UHD capability @ 60 Hz with 4:4:4 chroma sampling, plus support for HDR formats

- Ideal for with new and emerging 4K/UHD and HDR-capable sources and displays. Supports HDR10 @ 60 Hz and Dolby Vision @ 30 Hz, as well as HLG.
- Fully supports video resolutions, audio formats, and color space formats in the HDMI 2.0b specification.

### HDCP 2.2 compliant

- Adheres to latest specification for High-bandwidth Digital Content Protection.
- Allows protected content stream to pass between authenticated devices.

### HDBaseT receiver for HDMI, Ethernet, power, and control up to 330 feet (100 meters)

- Receives HDMI up to 330 feet (100 meters) @ 4K HDR using CAT6a/7 cable.
- Uses easy-to-integrate category cable for low-cost, reliable system installation.

### Remotely powered by Opus matrix switcher via PoE (Power over Ethernet)

- Power for receiver is supplied by an Opus Series matrix switcher over HDBaseT.
- Allows convenient receiver installation at a display or projector without the need for local AC power.

### Extends RS-232, IR, and Ethernet control signals over HDBaseT

- Bidirectional extension of RS-232, IR, and Ethernet control signals.
- Streamlines integration of control for displays.

### Visually lossless VESA Display Stream Compression

- Enables HDBaseT transmission of HDMI up to 18 Gbps using extremely light video compression.
- Innovative signal extension solution delivers very high, pristine image quality.

### Delivers return audio from a TV via dedicated HDBaseT audio return path

- Provides a return audio pathway from a television, via TOSLINK digital audio interface, back to the Opus matrix switcher over HDBaseT.
- Easy and convenient integration of television audio for over-the-air broadcasts, OTT (over-the-top) media services, and more.

### Integrated HDBaseT link status monitoring

- Continuously monitors integrity of the HDBaseT cable link between the Opus matrix switcher and receiver. Web GUI provides real-time link status, plus detailed HDBaseT and HDMI signal information.
- Quick, easy verification or troubleshooting of RJ-45 termination or twisted pair cable quality.

## Specifications

Ports	
HDMI OUT	Type A, 19-pin female, locking
HDBaseT IN	RJ45
TOSLINK IN/OUT	S/PDIF, Optical fiber connector
LAN	RJ45
DEBUG	Mini-USB
RS-232	3-pin captive screw
IR IN/OUT	2-pin captive screw

Video	
UHD/HD/SD	4096×2160@24/25/30/50/60Hz, 3840×2160@24/25/30/50/60Hz, 2048×1080p, 1080p@23.98/24/25/29.97/30/50/59.94/60Hz, 1080i@50/59.94/60Hz, 720p@50/59.94/60Hz, 576p, 576i, 480p, 480i
VESA	2560×2048, 2560×1600, 2048×1536, 1920×1200, 1680×1050, 1600×1200, 1600×900, 1440×900, 1400×1050, 1366×768, 1360×768, 1280×1024, 1280×800, 1280×768, 1152×768, 1024×768, 800×600
Color Space	YUV, RGB
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0
Color Depth	8-bit, 10-bit, 12-bit
HDR	HDR10 & HLG @ 60Hz and Dolby® Vision™ @ 30Hz

Audio	
HDMI OUT	PCM 2Ch, LPCM 5.1, LPCM 7.1, Dolby® Digital, DTS® 5.1, Dolby Digital Plus™, Dolby TrueHD, DTS-HD Master Audio™, Dolby Atmos®, DTS:X®
TOSLINK	PCM 2Ch, Dolby® Digital, DTS® 5.1
Sample Rate	32 kHz, 44.1 kHz, 48 kHz, 88.2 kHz, 96 kHz, 176.4 kHz, 192 kHz
Bit Rate	24-bit (max.)

Resolution / Distance	4K/UHD - Feet / Meters		1080p - Feet / Meters	
	HDMI IN / OUT	15	5	30
CAT-5e / CAT-6	295	90	330	100
CAT-6a / CAT-7	330	100	330	100

Signal	
Bandwidth	18 Gbps
HDMI	2.0
CEC	On output, by trigger
HDCP	up to 2.2

Temperature	Fahrenheit	Celsius
Operating	32 to 104	0 to 40
Storage	-40 to 158	-40 to 70
Humidity (RH)	20% to 90%, non-condensing	

Power	
PoE	Powered by compatible transmitters

Dimensions	Inches	Millimeters
H x W x D	1.02 x 6.86 x 3.51	26 x 174.2 x 89.16
H x W x D (w/ears)	1.02 x 1 x 3.51	26 x 1 x 89.16

Weight	Pounds	Kilograms
Device	0.99 lbs	0.45 kg

Certification	
Unit	CE, FCC