



Notes:

1. Material and Finish:
 - Coupler Ring: Polyester (Black); UL94 V-0
 - Plug Housing: Polyester (Black); UL94 V-0
 - Cable Gland: PA (Black), UL94 V-0
 - Cable Gland Rubber Ring: NBR, Color: Black
 - Cable Fitting: PA (Black), UL94 V-0
 - Interfacial Seal: Silicon, Color: White
2. Duplex LC Connector
 - Housing: PEI , UL94 V-0, Color: **SM Blue/MM Beige/APC SM Green**
 - Inner Sub Assembly: Zirconia, Metal and PTFE
 - Crimp Barrel: Brass, Nickel Plated
 - Ferrule: Brass, Nickel Plated
 - Dust Cap: PC, Color: White
 - Duplex LC Clip: PC, Color: Black
 - Protective Cap: Polyester (Black); UL94 V-0
 - Tether: Polycarbonate (Black)
 - Operating Temperature: -40°C to +85°C
3. IP67 rated when covered or fully mated with the appropriate mating connector
4. Accept 4.5mm to 8.0mm outside diameter fiber optic cable
5. RoHS compliant

Directive 2002/95/EC RoHS Compliant

Description	Part Number
Duplex LC Single Mode Plug Kit + Plug Cover Assembly	17-300200
Duplex LC Multi Mode Plug Kit + Plug Cover Assembly	17-300210
Duplex LC APC Single Mode Plug Kit + Plug Cover Assembly	17-300220

THIS DRAWING MAY NOT BE COPIED, OR REPRODUCED IN ANY WAY AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DOT NOT ALTER CAD DRAWING BY HAND	Customer:		Tolerance Unless otherwise specified		Scale: NTS	Dim. in mm
	Name		0 PLC ±0.30 1 PLC ±0.20 2 PLC ±0.10 3 PLC ±0.05 ANGLES ±1°			
	Approval Date		Autodesk Inventor		Material: See Notes	
	2011		Date		Title: IP67 Industrial Duplex LC Plug Kit + Plug Cover Assembly Plastic Version	
Draw. Mar. 04		Name		Drawing No.: 17K1A216		DIN A3
Appd. Mar. 04		J. Chaudry		Part No.: SEE P/N ABOVE		Sheet 1/1
Norm		D-old				
b Jul/12/2011		Vincent ke				
a original						
Rev. Changes		Date		Name		

