



ASSEMBLY	CONNECTIVITY
LC/UPC	SC/APC
A	B
B	A

ITEM NO	LENGTH
EL8801	1.00m
EL8802	2.00m
EL8803	3.00m
EL8805	5.00m
EL8810	10.00m

**NOTE:**

- 1.Insertion loss :SC/APC<0.25dB LC/UPC<0.25dB λ:1310&1550nm  
Return loss :SC/APC≥60dB LC/UPC≥50dB λ:1310&1550nm
- 2.Durability:500 matings
- 3.Operation temperature:-40°C to +85°C
- 4.SC connector according to IEC 61754-4  
LC connector according to IEC 61754-20

**ROHS  
Compliant**

LC/UPC --- SC/APC(8°) DX 2.0mm G657A1 LSZH Yellow

ITEM	Description	Q'TY
1	LC dust cover white	2 PCS
2	LC/UPC SM simplex connector blue	2 PCS
3	LC clip blue	1 PC
4	LC 2.0mm boot white	2 PCS
5	LC heat-shrink tubing white	1 PC
6	LC heat-shrink tubing yellow	1 PC
7	Breakout heat-shrink tubing black L=15mm	2 PCS
8	OD=2.0mm duplex G657A1 9/125 fiber optical cable LSZH Yellow	1 PC
9	SC 2.0mm boot green	2 PCS
10	SC clip green	1 PC
11	SC/APC(8°) SM simplex connector green	2 PCS
12	SC dust cover green	2 PCS

**ewent**  
BY INVENT

Designed by:	Yong Yu	Audit:	Qihua Cheng
Date:	2017-04-10	Approve:	Yong Huang
Unit:	mm	Sheet:	A4
Drawing NO:	SOP-ED-170410-03-V2		