




KSD-103 Series



Industrial 3-Port Fast Ethernet Media Converter Switches



The industrial rated KSD-103 Fast Ethernet switch series supports three switching-base segment communications and benefit the following applications and make fiber deployment easier :

- Copper to fiber bridging converter
- Multimode fiber to single mode fiber bridging converter
- Fiber cable extender
- Cascaded fiber networking

Key Features :

- Provide 3 switching-base network segments
- Auto MDI/MDI-X crossover function on the TP copper port
- Support IEEE 802.3x flow control for full-duplex operation
- Support Back-pressure flow control for half-duplex operation
- Wide operating temperature range for temperature critical environment
- Support DIN-rail mounting and panel mounting
- Provide two power input types to meet more application needs
- Accept wide power input voltage range for application flexibility
- Industrial-rated Emission and Immunity performance

Specifications :

Forwarding Method	Store-and-forward, Full wire speed switching
Packet Size	Support 1536 bytes max.
Packet Types	Transparent conversion with no modification to : - Standard IEEE 802.3 Ethernet packet frames - IEEE 802.1Q tagged packet frames - RSTP packet frames
TP Port	Shielded RJ-45 jack Auto MDI/MDI-X crossover function, auto-negotiation function Supports Cat. 5 UTP cable up to 100m
Fiber (FX) Port	Multimode ST, SC, Single mode SC, Bi-directional SC MMF 50/125µm, 62.5/125µm fiber cable, SMF 9/125µm cable 100Mbps Full-duplex, Far End Fault Indication support
Model Definition	KSD-103-A: 2 TP ports, 1 FX port, KSD-103-B: 1 TP port, 2 FX ports
Flow Control	IEEE 802.3x for full-duplex, Back pressure for half-duplex
LEDs	Power status, Port link/activity
DC Power Input	Screwed terminal block : 2 pairs of +/- contacts DC jack : -D 6.3mm / + D 2.0mm Voltage range : +7 - +50VDC, 4W max. @50V DC IN
Relay Output	Alarm events : power failure, specific fiber port link fault Interface : 2 terminal contacts (30VDC/1A max. or 120VAC/0.5A max.)
Dimension	28 x 82 x 95 mm, Weight : 250g



Ordering Information :

Model	KSD-103-A FX KSD-103-B FX1 FX2	Ref. Distance	Operating Temperature
-T	ST MMF	2km	-10 ~ 70°C
-C	SC MMF	2km	-10 ~ 70°C
-C1	SC MMF	2km	-20 ~ 70°C
-SA2	SC SMF	20km	-20 ~ 70°C
-SL2	SC SMF	20km	-20 ~ 70°C
-SL3	SC SMF	30km	-20 ~ 70°C
-SL4	SC SMF	40km	-20 ~ 70°C
-SL6	SC SMF	60km	-20 ~ 70°C
-W3515	Bi-Di SC SMF	15~20km	-20 ~ 70°C
-W5315	Bi-Di SC SMF	15~20km	-20 ~ 70°C
-C1SL2	FX1: SC MMF FX2: SC SMF	2km 20km	-20 ~ 70°C

EMI EMS Safety Environmental Tests :

Test	Standard	Specifications
FCC/EMI	FCC Rule Part 15	Class B
CE/EMC/EMI	EN55022, CISPR 22	Class B
CE/EMC/Harmonic	EN 61000-3-2	< 75 W
CE/EMC/VFF	EN 61000-3-3	Clause 5
CE/EMC/EMS	EN 55024	
ESD Test	IEC 61000-4-2	Contact : +/-4KV Air : +/-8KV
RS Test	IEC 61000-4-3	Strength : 10V/m
EFT/BURST	IEC 61000-4-4	Level 3 Power : +/-2KV Signal : +/-1KVV
Surge Immunity	IEC 61000-4-5	Power : 2KV Signal : 1KV
CS Test	IEC 61000-4-6	Level 3
Magnetic Field Imm.	IEC 61000-4-8	50Hz 100A/m
Voltage Dips Imm.	IEC 61000-4-11	Interruption : C Dips : B
Safety	EN 60950, IEC 60950	
Dielectric Voltage	IEEE 802.3	TP, 1500VAC/60sec.
Insulation Resistance	IEEE 802.3	TP, 500VDC/10Mohm
Cold Test	IEC 68-2-1 Test Ad	-20°C, 96hrs
Dry Heat Test	IEC 68-2-2 Test Bd	+70°C 40%RH 96hrs
Damp Heat Test	IEC 68-2-3	+60°C 90%RH 96hrs
Storage Test	IEC 68-2-48	-20°C 96hrs +85°C 40%RH 96hrs
Vibration Test	IEC 68-2-34	5~30Hz, 0.5g Operating



FCC Part 15, Class B
CISPR 22 Class B

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd.,
Hsi-chih, Taipei Hsien, Taiwan.
Tel : 886-2-2698-3878
Fax : 886-2-2698-3873
E-mail : kti@ktinet.com.tw
URL : http://www.ktinet.com.tw

KTI Networks Inc.

10415-A Westpark Drive, Houston,
TX 77042. U.S.A.
Tel : 1-713-266-3891
Fax : 1-713-914-0555
E-mail : contact@ktinet.com
URL : http://www.ktinet.com

Trademarks : All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

Housing	Enclosed metal with no fan
Mounting Support	DIN Rail mounting, Panel mounting
Temperature	Operating : -20°C ~ +70°C, Storage : -20°C ~ +85°C Relative Humidity : 5% ~ 95% non-condensing
Approval	FCC Class B, CE/EMC Class B, EN60950 safetyHousing

Fiber Optical Specification :

Model Ext.	FX & Cable	Wavelength	Tx Power	Rx Sensitivity	Rx Max.Power
KSD-103-A-xxx & KSD-103-B-xxx					
-T	ST MMF	1310nm	-19 ~ -14 dBm	-31 dBm	0 dBm
-C	SC MMF	1310nm	-19 ~ -14 dBm	-31 dBm	-14 dBm
-C1	SC MMF	1310nm	-20 ~ -14 dBm	-31 dBm	0 dBm
-SA2	SC SMF	1310nm	-15 ~ -8 dBm	-31 dBm	-7 dBm
-SL2	SC SMF	1310nm	-15 ~ -8 dBm	-30 dBm	-7 dBm
-SL3	SC SMF	1310nm	-15 ~ -8 dBm	-34 dBm	0 dBm
-SL4	SC SMF	1310nm	-5 ~ 0 dBm	-34 dBm	0 dBm
-SL6	SC SMF	1310nm	-5 ~ 0 dBm	-35 dBm	0 dBm
-W3515	Bi-Di SC SMF	TX 1310nm RX 1550nm	-14 ~ -8 dBm	-31 dBm	0 dBm
-W5315	Bi-Di SC SMF	TX 1550nm RX 1310nm	-14 ~ -8 dBm	-31 dBm	0 dBm
KSD-103-B-xxx					
-C1SL2	FX1 : SC MMF FX2 : SC SMF	1310nm 1310nm	-20 ~ -14 dBm -15 ~ -8 dBm	-31 dBm -30 dBm	0 dBm -7 dBm

