



NOTE:

1. CABLE:UL2725 3.0VER [(30#*1P+D+AL+M)*2C+28#*1P+24#*2C]+F+AL+B,OD=5.5mm,BLACK COLOR,PVC JACKET.(AM BRAID)
2. LENGTH:300mm.
3. CONNECTOR:USB 3.0 AF* 2PCS(NICKEL PLATED,BLUE INSULATOR),IDE 20P*1PCS(BLUE INSULATOR)
4. MOLD:BLACK MOLDING.
5. CONTACTS:

P1 (USB AF)	1	5	6	7	8	9	4	2	3	64	P3 (USB AF)	3	2	4	9	8	7	6	5	1	64
P2 (IDE20P)	1	2	3	4	5	6	7	8	9	4	P2 (IDE20P)	11	12	13	14	15	16	17	18	19	13

6. TESTING:100% TEST.
INSULATION:5M.

RoHS Compliant

Company	IBV		Goods Code			Draw	FC001 ZXW	Date	2011.05.18	
ITEM NO.	SB2406		Drawing Evidence:			Check		Date		
Goods NO.	S-*****		Unit(mm)			Approval		Date		
Original NO.	S-*****		Unit(mm)					Date		
						ATE		VER. A	REVISE	Date