



No. of Positions	Dimensions(mm)					
	A	B	C	D	E	F
9	30.81	24.99	16.92	16.33	11.09	10.16
15	39.14	33.32	25.50	24.66	19.39	17.78
25	53.04	47.04	38.96	38.38	33.24	30.48
37	69.32	63.50	55.42	54.84	49.86	45.72

Tolerances +/-0.15mm

- Insulator: Glass-filled thermoplastic, PBT, UL94V-0 rated
- Contact: Brass
- Contact resistance: 20mOhm max. at 1A DC
- Insulation resistance: 1000Mohm at 500V DC
- Dielectric withstanding voltage: 1000V ACrms 60Hz for 1 minute
- Current rating: 5A
- Voltage rating: 250V ACrms, 60Hz

Änderung	Datum	Name	Datum	Name
Tolerances completed	12.07.01	Hellwig	09.02.00	Hellwig
			09.02.00	<i>Hellwig</i>
			Norm.	

Benennung  
**D-Sub flat cable connector**  
 A-DFF... LP III/ Z  
 A-DSF... LP III/ Z

<b>ASSMANN</b> Electronic Components	Zeichnungsnummer	Blatt
	<b>ASS 0128 CO</b>	<b>1/2</b>
Ersatz für	ASS 0128 CO vom 08.10.1999	Blatt