

**Technical specification :**

Rated voltage: IEC 61076-2-101	12pos 30 V
Current rating: IEC 61076-2-101	1,5A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

**Materials:**

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Coupling screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

**Installation specification:**



Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

**Contact assignment:**

1 ■ brown	7 ■ black
2 ■ blue	8 ■ grey
3 ■ white	9 ■ red
4 ■ green	10 ■ violet
5 ■ pink	11 ■ grey-pink
6 ■ yellow	12 ■ red-blue

Part no:	Description:	Length L:	Cable:
43-11276	SAL - 12 - RS12 - 2 / K1	2m	TPU, UL 20549, black, 12x0,14mm <sup>2</sup> Cable: 781-K11120
43-11277	SAL - 12 - RS12 - 3 / K1	3m	
43-11278	SAL - 12 - RS12 - 5 / K1	5m	
43-11279	SAL - 12 - RS12 - 10 / K1	10m	
43-xxxxx	SAL - 12 - RS12 - ... / K1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: b 25.01.2011 VF Ä3767 Coupling screw modified, spanner flats added, data sheet modified	 dim. in mm	title:		
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%		date	name	Male connector M12x1 axial
	THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	drawn	12.10.07	Franz	
		appd.	12.10.07	Mankopf	43K1A552
			part no:		
			see table		