



2.0mm outer jacket LSZH Yellow
 900u buffer & G657A1 fiber
 Aramid yarn

| ASSEMBLY | CONNECTIVITY |
|----------|--------------|
| SC/UPC-1 | SC/UPC-2 |
| A | B |
| B | A |

| ITEM NO | LENGTH |
|---------|--------|
| EL.3901 | 1.00m |
| EL.3902 | 2.00m |
| EL.3903 | 3.00m |
| EL.3905 | 5.00m |
| EL.3910 | 10.00m |

NOTE:

1. Insertion loss : SC/PC ≤ 0.25dB λ: 1310&1550nm
Return loss : SC/PC ≥ 50dB λ: 1310&1550nm
2. Durability: 500 matings
3. Operation temperature: -40°C to +85°C
4. SC connector according to IEC 61754-4

**ROHS
Compliant**

SC/PC --- SC/PC DX 2.0mm G657A1 LSZH Yellow

| ITEM | Description | Q'TY |
|------|--|-------|
| 1 | SC dust cover lucency | 4 PCS |
| 2 | SC/PC SM simplex connector blue | 4 PCS |
| 3 | SC clip blue | 2 PCS |
| 4 | SC 2.0mm boot blue | 2 PCS |
| 5 | Breakout heat-shrink tubing black L=15mm | 2 PCS |
| 6 | OD=2.0mm duplex G657A1 9/125 fiber optical cable LSZH Yellow | 1 PC |

ewent
BY INVENT

| | | | |
|--------------|---------------------|----------|-------------|
| Designed by: | Yong Yu | Audit: | Qihua Cheng |
| Date: | 2017-04-08 | Approve: | Yong Huang |
| Unit: | mm | Sheet: | A4 |
| Drawing NO: | SOP-ED-170408-05-V1 | | |