

The AvediaStream e5640 delivers a 4K UHD stream in either HEVC or H.264 at up to 300Mbps. Capable of broadcast quality Ultra High Definition encoding from any of its interfaces, it is also capable of up to four independent 1080p60 HEVC encodes.



Interfaces

- 4x 3G-SDI
- HDMI 2.0
- DisplayPort 2.0x 802.3 100/1000 Ethernet (RJ-45) sockets

Video Input

- 4x Micro BNC (3G-SDI) Interface
 - 3840x2160p 60Hz / 59.94Hz / 50Hz / 30Hz / 29.97Hz / 25Hz / 24Hz*
 - 1920x1080p 60Hz / 59.94Hz / 50Hz / 30Hz / 29.97Hz / 25Hz / 24Hz
 - 1920x1080i 60Hz / 59.94Hz / 50Hz
 - 1280x720p 60Hz / 59.94Hz / 50Hz / 30Hz / 29.97Hz / 25Hz / 24Hz
- HDMI 2.0 / DisplayPort 1.2 Interface**
 - 3840x2160p 60Hz / 59.94Hz / 50Hz / 30Hz / 29.97Hz / 25Hz / 24Hz
 - 1920x1080p 60Hz / 59.94Hz / 50Hz / 30Hz / 29.97Hz / 25Hz / 24Hz
 - 1920x1080i 60Hz / 59.94Hz / 50Hz
 - 1280x720p 60Hz / 59.94Hz / 50Hz / 30Hz / 29.97Hz / 25Hz / 24Hz

* HEVC supports 2 Sample Interleave and Quadrant modes. H.264 supports Quadrant mode only

**Output: Auto scale to 3840x2160p60

Video Encoding

- MPEG-H part 2 H.265 (HEVC) (ISO/IEC 23008-2)
 - Main 10/Main profile @ Main/High tier
 - Level 1 – 6.2
- MPEG-4 part 10 H.264 (AVC) (ISO/IEC 14496-10)
 - Baseline, Main, Extended, High, Constrained Baseline,
 - Constrained High, Progressive High profile
 - Level 1 - 5.2
- MPEG-2 (ISO/IEC 13818-2)
 - Simple, Main, High profile
 - Low, Main and High levels
- Chroma 4:2:0
 - 4K UHD HEVC bitrate 3Mbps – 300Mbps
 - 4K UHD H.264 (AVC) 8Mbps – 100Mbps
 - Constant or variable bitrate



Audio Encoding

- AAC
- Bitrate: 64 - 320kbps
- Sample rate: 12kHz, 22.05kHz, 32kHz, 44.1kHz, 48kHz, 64kHz, 96kHz

Outbound Streams

- Single program MPEG-2 transport streams (ISO/IEC13818-1)
 - UDP
 - RTP
 - IP unicast
 - IP multicast
 - IGMP Join Group for enhanced switch compatibility

Output Container formats

- MPEG-2 Transport Stream (TS)

Outbound Channel Management

- Channel announcement via SAP/SDP
- Multicast/unicast address selection (automatic/manual)
- Configurable name, number and group membership

Management

- Fully integrated with Exterity management tools
- Network administration via SSH and SNMP
- HTTP web interface (supported browsers: Firefox, Internet Explorer and Chrome). Check with support@exterity.com for version information
- Serial RS232 Admin Port
- Event logging via Syslog (local and remote)
- Firmware upgrade via TFTP
- Configuration backup/restore via TFTP

Operating System

- Based on CentOS 7.1

Scaler

- H.264 (AVC) & MPEG-2 Video
 - User-configurable up/down scaling
 - User-configurable frame rate adjustment

Video Output Standards

- H.265 (HEVC) up to 2160p60 (3840x2160) or 4x1080p60
- H.264 (AVC) up to 2160p60 (3840x2160) or 4x1080p60
- MPEG-2 up to 1080p60

Audio Output Standards

- AAC
- Protocols
- IP (RFC 791), UDP (RFC 768), TCP (RFC 793), ARP (RFC 826), DNS (RFC 1035), DHCP (RFC 2131), ICMP (RFC 792), IGMP (RFC 3376), TFTP (RFC 1350), HTTP (RFC 2616), Syslog (RFC 3164), NTP (RFC 1305), SAP (RFC 2974), SDP (RFC 4566), RTP (RFC 3550), SNMP (v1, v2c -RFC 1901)

Regulatory

EMC:

- EN55022:2010, EN55024:2010
- EN61000-3-2:2006 + A1:2009 + A2:2009
- EN61000-3-3:2008
- IEC 60950-1:2005 (Ed. 2.0) + Am 1:2009 +Am 2:2013
- EN60950-1 2006 + A11:2009, A1:2010, A12:2011, A2:2013

FCC/UL/CSA:

- FCC 47 CFR Part 15 Subpart B: 2008; ANSI C63.4-2003
- UL60950-1/CSA C22.2 No. 60950-1, Second Edition. Rev. October 14, 2014

Environment

- Operating temperature range: 5° - 35°C (41° to 95°F)
- Non-operating temperature range: -40° to 60°C (-40° to 140°F)
- Operating humidity range: 8% to 90% (noncondensing)
- Non-operating humidity range: 5% to 95% (noncondensing)

Physical Format

- Compact 1U rack-mounted standard 19" chassis
- Dimensions: W: 483mm x D: 369mm x H: 43mm
- Weight: 6.55kg

Power

- 290W Typical, 430W Maximum
- MTBF
- Calculated to MIL-HDBK-217F, Notice 2: 85733 hours (9.8 years)

		e2320	e3730 -std	e3730 -hdcp-32	e3730 -hdcp-pro	e3732 -std	e3732 -hdcp-32	e3732 -hdcp-pro	e3655	e3555	e5640	
INPUT	Source	IR Out (source control)	✓	✓	✓	✓	✓	✓				
		Inputs	2	1	1	1	2	2	2	1	1	4
	Video Input	Composite	✓									
		S-Video	✓									
		SD Component	✓									
		RGBS	✓									
		HDMI		✓	✓	✓	✓	✓	✓			✓
		SDI (SD,HD,3G)								✓	✓	4
		Display Port										✓
	Audio Input	Line Level Stereo	✓									
HDMI			✓	✓	✓	✓	✓	✓	✓	✓	✓	
S/PDIF									✓	✓		
OUTPUT	Encoding	UHD 2160p									✓	
		HD 1080p		✓	✓	✓	✓	✓		✓	✓	
		HD 1080i/720p		✓	✓	✓	✓	✓	✓	✓	✓	
		SD	✓	✓	✓	✓	✓	✓	✓	✓	✓	
		HEVC										✓
		H.264	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
		MPEG-2	✓							✓		✓
		HDCPv2 Content Protection			✓			✓				
		HDCP Professional Content Protection				✓			✓			
		Video Scaler	✓		✓	✓		✓	✓	✓	✓	✓
		MPEG-1 Layer II Audio	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
		Stereo AAC Audio		✓	✓	✓	✓	✓	✓	✓	✓	✓
		Streaming	UDP Multicast	✓	✓	✓	✓	✓	✓	✓	✓	✓