



KGC-311 Series



Multimode to Single Mode Optical Fiber Media Converters

Product Highlights:

- Full wire speed performance
- SFP flexibility
- Low power consumption
- Optional Din-Rail mounting
- Center Chassis installation support
- Options for Bi-Di communication

KC-3DR :
Din-Rail mounting bracket



KC-1300 :
Managed center chassis



Key Features:

- Complies with IEEE 802.3z 1000Base-SX/LX and IEEE 802.3u 100Base-FX standard
- Provides media conversion between single mode and multimode optical fiber media types
- Supports both 1000Mbps Gigabit Ethernet fiber and 100Mbps Fast Ethernet fiber applications
- Provides two SFP slots and supports standard SFP fiber transceivers
- Support center chassis installation with advantages of central power, power redundancy and management
- Provides LEDs for easy network monitoring

Specifications:

Standard	IEEE 802.3z 1000Base-SX/LX, IEEE 802.3u 100Base-FX
Fiber Ports	MM port: SFP-A slot for Multimode fiber transceiver SM port: SFP-B slot for Single mode fiber transceiver
Fiber Cable	MM port: MMF 62.5/125µm, 50/125µm SM port: SMF 9/125µm
LEDs	Power status, GE / FE status MM port optical link status, SM port optical link status
Mounting	Desktop, Wall, Din-Rail (optional), Center chassis
Center Chassis	Up to 16 units in one KC-1300 rack chassis Support optional power redundancy and management
Power Input	+5 ~ +12VDC (+/-5%), Consumption 2W max.@7.5V
Environment	Operation Temperature: -5°C ~ 55°C Storage Temperature -20°C ~ 85°C Relative Humidity: 10% ~ 70% non-condensing
Dimension	108 x 72.5 x 23 mm (WxDxH)
Compliance	FCC Class A, CE mark, CISPR 22 Class A

Fiber Ordering Information:

Model Ext#	Port Type	Port Tx Power (dBm)	Connector	Rx Sensitivity (dBm)	Wavelength (nm)	Ref. Distance
FE 100Mbps series						
-FSL3	MM	-20 ~ -14	LC	-31	1310	2 km
	SM	-15 ~ -8	LC	-34	1310	30 km
-FSL6	MM	-20 ~ -14	LC	-31	1310	2 km
	SM	-5 ~ 0	LC	-35	1310	60 km



Ordering Information:

Model: KGC-311	FE/GE	MM Port	SM Port
-FSL3	FE	2km	30km
-FSL6	FE	2km	60km
-FSL10	FE	2km	100km
-FW3520	FE	2km	Tx 1310nm Bi-Di 20km
-FW5320	FE	2km	Tx 1550nm Bi-Di 20km
-LX	GE	200/500m	10km
-LX20	GE	200/500m	20km
-LX30	GE	200/500m	30km
-LX50	GE	200/500m	50km
-LX70	GE	200/500m	70km
-W3510	GE	200/500m	Tx 1310nm Bi-Di 10km
-W5310	GE	200/500m	Tx 1550nm Bi-Di 10km
-W3410	GE	200/500m	Tx 1310nm Bi-Di 10km
-W4310	GE	200/500m	Tx 1490nm Bi-Di 10km
-W3520	GE	200/500m	Tx 1310nm Bi-Di 20km
-W5320	GE	200/500m	Tx 1550nm Bi-Di 20km



FCC Part 15, Class A
CISPR 22 Class A

Katron Technologies Inc.

15F-7, No. 79, Sec. 1, Hsin Tai Wu Rd., Hsi-chih, Taipei Hsien, Taiwan.
Tel: 886-2-2698-3878
Fax: 886-2-2698-3873
E-mail: kti@ktinet.com.tw
URL: http://www.ktinet.com.tw

KTI Networks Inc.

7400 Harwin Dr., Suite 120 Houston, Texas
77036 U.S.A.
Tel: 713-266-3891
Fax: 713-914-0555
E-mail: kti@ktinet.com
URL: http://www.ktinet.com

Trademarks: All brand names are trademarks or registered trademarks of their respective holders.
This information is subject to change without prior notice.

-FSL10	MM	-20 ~ -14	LC	-31	1310	2 km
	SM	-5 ~ 0	LC	-35	1550	100 km
-FW3520	MM	-20 ~ -14	LC	-31	1310	2 km
	SM	-14 ~ -8	Bi-Di LC	-32	Tx 1310 Rx 1550	20 km
-FW5320	MM	-20 ~ -14	LC	-31	1310	2 km
	SM	-14 ~ -8	Bi-Di LC	-32	Tx 1550 Rx 1310	20 km
GE 1000Mbps series						
-LX	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-9.5 ~ -3	LC	-20	1310	10 km
-LX20	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-8 ~ -2	LC	-23	1310	20 km
-LX30	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-4 ~ +3	LC	-23	1310	30 km
-LX50	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-4 ~ +1	LC	-23	1550	50 km
-LX70	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	0 ~ +5	LC	-23	1550	70 km
-W3510	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-9 ~ -3	Bi-Di LC	-21	Tx 1310 Rx 1550	10 km
-W5310	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-9 ~ -3	Bi-Di LC	-21	Tx 1550 Rx 1310	10 km
-W3410	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-9 ~ -3	Bi-Di LC	-21	Tx 1310 Rx 1490	10 km
-W4310	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-9 ~ -3	Bi-Di LC	-21	Tx 1490 Rx 1310	10 km
-W3520	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-8 ~ -3	Bi-Di LC	-23	Tx 1310 Rx 1550	20 km
-W5320	MM	-9.5 ~ -4	LC	-18	850	200m/500m
	SM	-8 ~ -3	Bi-Di LC	-23	Tx 1550 Rx 1310	20 km

* GE: Gigabit Ethernet, FE: Fast Ethernet

* 200m/500m: 200 meters with MMF 62.5/125, 500 meters with MMF 50/125