


**MALE HEADER, ANGLED  
PITCH 2.54x2.54mm  
ACC. TO EN 60603-13**




Contacts:	Copper alloy
Finish:	RL1-RL3: gold plated
	RL4: tin plated
Insulator:	PBT 20% GF
Withstanding voltage:	1000V DC or AC peak
Current rating:	1.0A
Contact resistance:	20mOhm
Insulation resistance:	5000MOhm at 100V
	Life:
	RL2: 250 mating cycles
	RL3: 50 mating cycles
	RL4: 50 mating cycles

**Accessories:**

Latch (short): SPMH-LC-SHORT  
 Latch (long): SPMH-LC-LONG

60pol. connectors  
 upon request



B with short latches: 23.1mm  
 B with long latches: 26.6mm

No. of Contacts	10	14	16	20	26	34	40	50
A [mm]	32.2	37.2	39.8	44.9	52.5	62.6	70.3	83.0

**SPMHxxA-3000**

Latches:	not used	0 (Standard)
		0 = without latches
		1 = with short latches
		2 = with long latches
Pin length:		0 = 2.9mm (Standard)
		1 = 4.5mm
Requirement level:		1 = RL1 = gold plated, 500 mating cycles
		2 = RL2 = gold plated, 250 mating cycles
		3 = RL3 = gold plated, 50 mating cycles
		4 = RL4 = tin plated, 50 mating cycles
Style:		A = Angled
No. of contacts		

