



Property of ACT

PARTNO.	Length
RL3200	0,5 mtr
RL3201	1 mtr
RL3251	1,5 mtr
RL3202	2 mtr
RL3252	2,5 mtr
RL3203	3 mtr
RL3205	5 mtr
RL3207	7 mtr
RL3210	10 mtr

PIN LAYOUT		Description	Fiber	ITEM	PART NO.	DESCRIPTION	QTY/MTR
Conector		Cable Color	Yellow	1	..	E2000Male Connector APC8°	1
A	●-----●	Category	OS2	2	..	E2000 Male Connector APC8°	1
B	●-----●	Fiber Diameter	9/125μ	3	..	LC Male Connector UPC	1
		Type Fiber Cable	Patch Cord Duplex	4	..	LC Male Connector UPC	1
		Category	G.657A1	5	..	OS2 G.657A1 Fiber Duplex	XX mtr
		Min. operating temperature	-20	..	..	..	..
		Max. operating temperature	+60	..	..	..	..
		Jacket	LSZH	..	..	..	..
		Insertion Loss	Average <0.12dB, Max. ≤0.25dB	..	..	..	..
		Return Loss	APC ≤65dB, UPC ≤55dB	..	..	..	..
		OD	2.00 mm	..	..	..	..
		..	..	..	..	..	..
		..	..	..	..	..	..

STATUS: **Final**

SIGNED:

TITLE: **E2000/APC8° - LC/UPC 9/125 OS2 duplex patchcable**

DRAWN BY: Gerard van Eede	DRAW DATE: 20-01-2020	REVISED: 10-4-2020	REV: 1.00
---------------------------	-----------------------	--------------------	-----------

PROJECT NR: XXXXX-XXXX PAGE 1 / 1

Unless otherwise specified: Dimensions are in millimeters