DVI Input Module for CORIOmaster

Dual DVI Universal input module

CM-DVIU-2IN

OVERVIEW

The CM-DVIU-2IN module for CORIOmaster can accept resolutions from analog up to 1920x1200 @ 60Hz. DVI-U accepts digital and analogue video as well as audio and can be used with a wide range of adapters for a wide range of connections.

KEY FEATURES

- ◆ Accepts resolutions up to 1920x1200P @ 60Hz
- Support via DVI adapter for HDMI, VGA, composite video,
 YUV and S-Video
- Audio Support
- ◆ HDCP Compliant



Designed For

C3-540 CORIOmaster,
C3-510 CORIOmaster Mini,
C3-503 CORIO master Micro

Module installs in to any of the input slots

Max Installable

	C3-540 CORIOmaster 14x,
CODIOmanatar	C3-510 CORIOmaster Mini
CORIOmaster	5x, C3-503 CORIOmaster
	Micro 2x

Constraints

None	Can be installed with other types modules in the same system
------	--

SPECIFICATIONS

Inputs	2x DVIU (Universal DVI)
Resolution Support	640x480p (60, 72, 75, 85Hz), 720x487i (59.94Hz), 720x480i (59.94Hz), 720x480p (59.94Hz), 720x576i (50Hz), 720x576p (50Hz), 800x600p (56, 60, 72, 75, 85Hz), 980x980p (75Hz), 1024x768p (60, 70, 75, 85Hz), 1152x864p (70, 75Hz), 1280x720p (23.98, 24, 25, 29.97, 30, 50, 60Hz), 1280x768p (60, 75, 85Hz), 1280x800p (60, 75, 85Hz), 1280x960p (60, 85Hz), 1280x1024p (50, 60, 75, 85Hz), 1360x768p (60Hz), 1366x768p (60Hz) 1400x900p (60Hz), 1400x1050p (50, 60, 75Hz), 1440x900p (60, 75, 85Hz), 1600x900p (60Hz), 1600x1200p (60Hz), 1680x1050p (60Hz), 1920x720p (60Hz), 1920x1080i (47.96, 48, 50, 59.94, 60Hz), 1920x1080p (23.98, 24, 25, 29.97, 30, 50. 59.94, 60Hz), 1920x1200p (50, 60Hz)
Compatibility	DVI, HDMI, RGB/YPbPr, YC, CV
Color Space	BT.601 on standard resolutions BT.709 for 720p, 1080i and 1080p
AUDIO	
Supported Sampling Rate	48KHz
Sample Size	24 bits
Supported Channels	1 Stereo pair on each input

